


43F-43F

Coaxial Adapter 4.3-10 Female - 4.3-10 Female

43F-43F

Coaxial Adapter, 4.3-10 Female / 4.3-10 Female



STRUCTURE

Product Line		Coaxial Cable Components
Product Type		Coaxial Adapter
Coaxial Cable Type		Foam Dielectric, Ultraflexible Foam Dielectric , Radiating Cable

MECHANICAL SPECIFICATIONS

Connector A		4.3-10 Female
Center Contact Connector A		Copper Alloy, silver plated
Outer Contact Connector A		Copper Alloy, CuSnZn plated
Connector B		4.3-10 Female
Center Contact Connector B		Copper Alloy, silver plated
Outer Contact Connector B		Copper Alloy, CuSnZn plated
Dielectric		PTFE
Sealing class		IP68, connected

ELECTRICAL SPECIFICATIONS

Frequency Range - MHz		DC - 6000
VSWR, Return Loss	VSWR (dB)	DC TO 2GHz VSWR 1.04 (34.15) 2 TO 3GHz VSWR 1.06 (30.71) 3 TO 6GHz VSWR 1.10 (26.44)
Insertion Loss, dB (Max)	dB	0.05
3rd Order IM Product @ 2x20 Watts	dBc	< -163

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-45 to 85 (-49 to 185)
-----------------------	---------	------------------------



43F-43F

Coaxial Adapter 4.3-10 Female - 4.3-10 Female

43F-43F

PACKAGING INFORMATION

Package Quantity		1
------------------	--	---