

PlenumS-CONN-DB75IC

3/4" Steel Saddle Connector for PlenumShield Armored 1/2" ClearFill®Line Aluminum Plenum-Rated Air-Dielectric Coaxial Cable

PlenumS-CONN-DB75IC

3/4" Steel Saddle Connector for PlenumShield Armored ClearFill®Line 1/2" low-loss air dielectric cable



FEATURES & BENEFITS

- Connect PlenumShield cable to the JBox.
- 3/4 in. Zinc Plated Steel Saddle Connector with Insulated Throat.
- Is made from high-strength steel and finished with zinc plating to offer exceptional resistance to corrosion.
- Insulated throat ensures PlenumShield are safeguarded against any potential damage and maintaining the integrity of connections even in demanding conditions.
- Designed for use with 3/4" flexible metal conduits, armored cables, and metal-clad cables.

APPLICATIONS

Applications	PlenumShield to JBox	In Building	DAS	NFPA 72 section 12.4.2 Pathway Survivability Level 1
--------------	----------------------	-------------	-----	--

STRUCTURE

Cable Type	PlenumShield, Air-Dielectric, Corrugated, Armored Cable
------------	---

TESTING AND ENVIRONMENTAL

Regulatory Compliance	NFPA 72 section 12.4.2 Pathway Survivability Level 1
-----------------------	--

PlenumS-CONN-DB75IC

3/4" Steel Saddle Connector for PlenumShield Armored 1/2" ClearFill®Line Aluminum Plenum-Rated Air-Dielectric Coaxial Cable

PlenumS-CONN-DB75IC

ADDITIONAL IMAGES

