

**CLAMP-495-S**

Cable hanger, non-insulated, bolt-on, for 5" coaxial cable

Hanger, non-insulated, bolt-on for coaxial cable

HCA495, made of stainless steel

**FEATURES / BENEFITS**

Stainless steel hangers for supporting coaxial cable to tower. Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot

**Technical features****GENERAL SPECIFICATIONS**

|                        |  |                           |
|------------------------|--|---------------------------|
| Product Line           |  | Coaxial Cable Accessories |
| Product Type           |  | Hanger                    |
| Hanger Type            |  | Bolt-On, non-insulated    |
| Transmission Line Type |  | HCA495                    |
| Cable Type             |  | Air Dielectric            |

**MECHANICAL SPECIFICATIONS**

|                                     |        |                      |
|-------------------------------------|--------|----------------------|
| Cable Size                          |        | 5"                   |
| Number of Cable / Waveguide Runs    |        | 1                    |
| Material                            |        | Stainless Steel      |
| Recommended / Maximum Clamp Spacing | m (ft) | 0.8 / 1.2 (2.75 / 4) |

**TEMPERATURE SPECIFICATIONS**

|                       |         |                         |
|-----------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185 ) |
| Storage Temperature   | °C (°F) | -50 to 85 (-58 to 185 ) |

**PACKAGING INFORMATION**

|                  |  |   |
|------------------|--|---|
| Package Quantity |  | 1 |
|------------------|--|---|

**External Document Links****Notes**

If using the Bolt-on hanger series in vertical runs, the hoisting grips need to be kept on the tower.